

Direct Color Systems®

"Leading Manufacturer of Direct to Substrate Small Format Printers"



Garment Transfer Material

Direct Color Systems® GTM



GTM is Direct Color Systems' garment transfer material, available in both sheet for the Direct Jet flat bed solvent printers and roll format for the Flex33 printers. Images are designed and printed "right-reading." There is no need to mirror the image. After 24 hours, the garment can be washed and ironed. DCS's GTM is suitable for:

- Cotton
- Polyester
- Acrylic
- Blended garments

Available sizes:

GTM Sheets are 11"x17" (279mm x 432mm)

GTM Rolls are 12" x 25' (309mm x 7.6m) with a 3" core

For information on printers, contact Direct Color Systems +1 860-829-2244 or go to www.DirectColorSystems.com

Print



OR




Cut

with registration marks



Press



Wear





DCS 99A Hammer Mill Rd, Rocky Hill, CT USA 06067 / 800-693-6376 / +1 860-829-2244 / info@directcolorsystems.com

www.DirectColorSystems.com

Made in the USA. Distributed Globally.



Sample Cost

Image	Image size	Material	GTM Cost	Masking Cost	Ink Type	Ink Cost	Total Cost (not incl. garment)
	4"x4.5"	GTM Sheet FS-DJ-TRANS-25	\$0.32 (assuming 8 on a sheet)	0.05	IR4	\$0.02	\$0.39
	3.33"x4"	GTM Roll FM-DRKSOL-1225	\$0.27 (assuming 6 on an 9" feed)	0.04	IR8	\$0.05	\$0.36

GTM Specifications

	GTM Sheet for the Direct Jet line of Printers	GTM Roll for the Flex line of printers
Size	11"x17" (279mm x 432mm)	12" x 25' (309mm x 7.6m)
Cutting	45° blade with approximately 70 grams of force	45° blade with approximately 70 grams of force
Press temperature	150-170°C (302-335°F)	191°C (375°F)
Press time	20-30 seconds	20 seconds
Wash	After 24 hours	After 24 hours
Iron	Inside only, avoid the transfer	Inside only, avoid the transfer
Dry Clean	No	No
Storage	Up to one year in a dry room, 15-30°C (59-86°F). Keep protected from sunlight and excessive humidity.	Up to one year in a dry room, 15-30°C (59-86°F). Keep protected from sunlight and excessive humidity.

GTM Equipment & Accessories

Part Number	Description
DJ-1309/1314/1324	Flatbed Solvent Printer with Automatic Height Adjust
DJ-2-17	Flatbed Solvent Printer with Manual Height Adjust
Flex33	Flexible Media Printer
EQ-ROBOPRO	Graphtec RoboPRO Cutter
DCS-DK20S	Heat Press 16x20 Swinger (110V or 220V)
DCS-JP14	Heat Press 12x14 Swinger (110V or 220V)
FM-FXETEFLONSHT	Teflon Sheet 18"x20"
FM-MAPGXF10015	High Tack Clear Mask 15"x100'
FM-HTTK1000	Vinyl Weeding Tool Kit
AC-SQUEEGEE	Vinyl Squeegee
AC-SLEEVE-SQG	Felt Sleeve for Squeegee

DCS 99A Hammer Mill Rd, Rocky Hill, CT USA 06067 / 800-693-6376 / +1 860-829-2244 / info@directcolorssystems.com

