

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Page 1/10

1 Identification

Product identifier

Product name: ADApt G5/G6, UVInk, Varnish, L

Article number: I-4820-VA Application of the substance / the mixture: Printing inks

Details of the supplier of the safety data sheet

Direct Color Systems 99 Hammer Mill Rd. Rocky Hill, CT 06067-USA Manufacturer/Supplier: Direct Color Systems 99 Hammer Mill Rd. Rocky Hill, CT 06067-USA Emergency telephone number US: 24/7 CHEMTREC 1-800-424-9300 Emergency telephone number International: 24/7 CHEMTREC +1 703-527-3887

2 Hazard(s) identification

Classification of the substance or mixture

Acute Toxicity - Oral 4	H302 Harmful if swallowed.			
Skin Corrosion 1C	H314 Causes severe skin burns and eye damage.			
Eye Damage 1	H318 Causes serious eye damage.			
Sensitization - Skin 1	H317 May cause an allergic skin reaction.			
Toxic to Reproduction 1B H360 May damage fertility or the unborn child.				

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



Signal word Danger

Hazard-determining components of labeling: 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester Tetrahydrofurfuryl Acrylate 2-phenoxyethyl acrylate Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Neopentylglycol(PO)2 Diacrylate propylidynetrimethanol, propoxylated, esters with acrylic acid hexamethylene diacrylate Hazard statements Harmful if swallowed. Causes severe skin burns and eye damage.

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

Μ	lay cause an allergic skin reaction.
Μ	lay damage fertility or the unborn child.
P	recautionary statements
0	btain special instructions before use.
D	o not handle until all safety precautions have been read and understood.
D	o not breathe dusts or mists.
W	Vash thoroughly after handling.
	o not eat, drink or smoke when using this product.
	ontaminated work clothing must not be allowed out of the workplace.
	Vear protective gloves/protective clothing/eye protection/face protection.
	swallowed: Call a poison center/doctor if you feel unwell.
	swallowed: Rinse mouth. Do NOT induce vomiting.
	on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF	FINHALED: Remove person to fresh air and keep comfortable for breathing.
If	in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continu
	nsing.
In	nmediately call a poison center/doctor.
	Exposed or concerned: Get medical advice/attention.
	pecific treatment (see on this label).
	skin irritation or rash occurs: Get medical advice/attention.
W	Vash contaminated clothing before reuse.
	tore locked up.
	ispose of contents/container in accordance with local/regional/national/international regulations.
	ditional information:
2	

6.3 % of the mixture consists of component(s) of unknown toxicity.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
86273-46-3 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester	≥ 25 - ≤ 50%	
Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317		
48145-04-6 2-phenoxyethyl acrylate	10 - 25%	
Toxic to Reproduction 2, H361; Sensitization - Skin 1A, H317		
84170-74-1 Neopentylglycol(PO)2 Diacrylate	2.5 - 10%	
Sensitization - Skin 1, H317		
75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	2.5 - 10%	
Toxic to Reproduction 2, H361		
2399-48-6 Tetrahydrofurfuryl Acrylate		
Toxic to Reproduction 1B, H360; Skin Corrosion 1C, H314; Eye Damage 1, H318; Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317; Flammable Liquids 4, H227		
53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid		
Eye Irritation 2A, H319; Sensitization - Skin 1, H317		
13048-33-4 hexamethylene diacrylate		
Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	US	

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment. **Special hazards arising from the substance or mixture** No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. **Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. 7 Handling and storage

Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires: Keep respiratory protective device available.

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements. **Information about storage in one common storage facility:** Not required. **Further information about storage conditions:** Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see section 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

13048-33-4 hexamethylene diacrylate

WEEL Long-term value: 1 mg/m³

DSEN

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

LIC

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and che General Information Appearance:	mical properties		
Form:	Liquid		
Color: Odor:	Clear Characteristic		
Odor threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.		
Flash point:	Not applicable.		
Flammability (solid, gaseous):	Not applicable.		
Decomposition temperature:	Not determined.		
Ignition temperature:	Product is not selfigniting.		
Danger of explosion:	Product does not present an explosion hazard.		
Explosion limits: Lower: Upper:	Not determined. Not determined.		
Vapor pressure:	Not determined.		
Density: Relative density Vapor density Evaporation rate	Not determined. Not determined. Not determined. Not determined.		
Solubility in / Miscibility with Water:	Fully miscible.		
Partition coefficient (n-octanol/water): Not determined.			
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.		
Other information	No further relevant information available.		

10 Stability and reactivity

Reactivity No further relevant information available. Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 1,086 - 1,101 mg/kg

86273-46-3 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester

Oral LD50 500 mg/kg (ATE)

2399-48-6 Tetrahydrofurfuryl Acrylate

Oral LD50 928 mg/kg (rat)

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid

Oral LD50 > 2,000 mg/kg (rat)

13048-33-4 hexamethylene diacrylate

Oral LD50 > 5,000 mg/kg (rat)

Dermal LD50 > 3,000 mg/kg (rab)

Primary irritant effect:

on the skin: Caustic effect on skin and mucous membranes.

on the eye: Strong caustic effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate: 2B

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available. Persistence and degradability No further relevant information available. Behavior in environmental systems: Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available. Ecotoxical effects: Remark: Harmful to fish according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

Additional ecological information:

General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations. **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

UN-Number DOT IMDG, IATA UN proper shipping name DOT IMDG

IATA

Transport hazard class(es)

DOT

Class

Class

Label

Packing group DOT

IMDG, IATA

not regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate, Neopentylglycol(PO)2 Diacrylate), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl acrylate, Neopentylglycol(PO)2 Diacrylate)

not regulated

not regulated UN3082

9 Miscellaneous dangerous substances and articles 9

not regulated III

IMDG, IATAIIIEnvironmental hazards:IIIMarine pollutant:Symbol (fish and tree)Special marking (IATA):Symbol (fish and tree)Special precautions for userWarning: Miscellaneous dangerous substances and articlesHazard identification number (Kemler code): 90

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

EMS Number:	F-A.S-F
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (2-PHENOXYETHYL ACRYLATE,
	NEOPENTYLGLYCOL(PO)2 DIACRYLATE), 9, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. SARA Section 355 (extremely hazardous substances): None of the ingredients is listed. Section 313 (Specific toxic chemical listings): None of the ingredients is listed. TSCA (Toxic Substances Control Act): 86273-46-3 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester: ACTIVE 48145-04-6 2-phenoxyethyl acrylate: ACTIVE 84170-74-1 Neopentylglycol(PO)2 Diacrylate: ACTIVE 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide: ACTIVE 53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid: ACTIVE 13048-33-4 hexamethylene diacrylate: ACTIVE Hazardous Air Pollutants 67-56-1 methanol **Proposition 65** Chemicals known to cause cancer: 15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. Chemicals known to cause developmental toxicity: 67-56-1 methanol **Carcinogenic categories** EPA (Environmental Protection Agency) 110-82-7 cvclohexane: I TLV (Threshold Limit Value) None of the ingredients is listed. NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



Signal word Danger

Hazard-determining components of labeling:

2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester Tetrahvdrofurfurvl Acrvlate 2-phenoxyethyl acrylate Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Neopentylglycol(PO)2 Diacrylate propylidynetrimethanol, propoxylated, esters with acrylic acid hexamethylene diacrylate Hazard statements Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May damage fertility or the unborn child. **Precautionary statements** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dusts or mists. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H227 Combustible liquid. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage.

US

US

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 11/16/2023

Version: 1.1

Reviewed on 11/16/2023

Product name: ADApt G5/G6, UVInk, Varnish, L

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H360 May damage fertility or the unborn child.
H361 Suspected of damaging fertility or the unborn child.
Contact:
Date of preparation / last revision 11/16/2023
Abbreviations and acronyms:
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flammable Liquids 4: Flammable liquids – Category 4
Acute Toxicity - Oral 4: Acute toxicity – Category 4
Skin Corrosion 1C: Skin corrosion/irritation – Category 1C
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Damage 1: Serious eye damage/eye irritation – Category 1
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - Skin 1: Skin sensitisation – Category 1
Sensitization - Skin 1A: Skin sensitisation – Category 1A
Toxic to Reproduction 1B: Reproductive toxicity – Category 1B
Toxic to Reproduction 2: Reproductive toxicity – Category 2
* Data compared to the previous version altered.