

Safety Data Sheet

Date of issue: 08/08/2025 according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Version: 2.0

Reviewed on 08/08/2025

*** 1 Identification****Product identifier****Product name:** ADapt G5/G6, UVInk, Varnish, L**Other means of identification****Article number:** I-4820-VA**Application of the substance / the mixture:** Printing inks**Details of the supplier of the safety data sheet**

Direct Color Systems

99 Hammer Mill Rd.

Rocky Hill, CT 06067-USA

Manufacturer/Supplier:

Direct Color Systems

99 Hammer Mill Rd.

Rocky Hill, CT 06067-USA

Emergency telephone number US: 24/7 CHEMTREC 1-800-424-9300**Emergency telephone number International:** 24/7 CHEMTREC +1 703-527-3887*** 2 Hazard(s) identification****Classification of the substance or mixture**

Acute toxicity - oral 4 H302 Harmful if swallowed.

Skin corrosion 1C H314 Causes severe skin burns and eye damage.

Eye damage 1 H318 Causes serious eye damage.

Sensitization - skin 1 H317 May cause an allergic skin reaction.

Reproductive toxicity 1B H360 May damage fertility or the unborn child.

Label elements**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS05 GHS07 GHS08

Signal word Danger**Hazard-determining components of labeling:**

2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester

Tetrahydrofurfuryl Acrylate

2-phenoxyethyl acrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Neopentylglycol(PO)2 Diacrylate

propylidynetrimethanol, propoxylated, esters with acrylic acid

hexamethylene diacrylate

Hazard statements

Harmful if swallowed.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

6.3 % of the mixture consists of component(s) of unknown toxicity.

Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

86273-46-3	2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester	≥ 25 - ≤ 50%
	Acute toxicity - oral 4, H302; Sensitization - skin 1, H317	
48145-04-6	2-phenoxyethyl acrylate	10 - 25%
	Reproductive toxicity 2, H361; Sensitization - skin 1A, H317	
84170-74-1	Neopentylglycol(PO)2 Diacrylate	2.5 - 10%
	Sensitization - skin 1, H317	
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	2.5 - 10%
	Reproductive toxicity 1B, H360; Sensitization - skin 1B, H317	
2399-48-6	Tetrahydrofurfuryl Acrylate	2.5 - 10%
	Reproductive toxicity 1B, H360; Skin corrosion 1C, H314; Eye damage 1, H318; Acute toxicity - oral 4, H302; Sensitization - skin 1, H317; Flammable liquids 4, H227	

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid	2.5 - 10%
Eye irritation 2A, H319; Sensitization - skin 1, H317	
13048-33-4 hexamethylene diacrylate	≥ 0 - ≤ 10%
Skin irritation 2, H315; Eye irritation 2A, H319; Sensitization - skin 1, H317	

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires: Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

13048-33-4 hexamethylene diacrylate

WEEL Long-term value: 1 mg/m³

DSEN

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Appropriate engineering controls No further data; see section 7.

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

Eye protection:



Tightly sealed goggles

* 9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Physical state	Liquid
Color:	Clear
Odor:	Characteristic
Odor threshold:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flammability:	Not applicable.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	
Kinematic:	Not determined.
Dynamic:	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/water):	Not determined.
Vapor pressure:	Not determined.
Vapor pressure:	
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Particle characteristics	Not applicable.

Other information

Appearance:	
Form:	Liquid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

*11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 1,086 - 1,101 mg/kg

86273-46-3 2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester

Oral LD50 500 mg/kg (ATE)

2399-48-6 Tetrahydrofurfuryl Acrylate

Oral LD50 928 mg/kg (rat)

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid

Oral LD50 > 2,000 mg/kg (rat)

13048-33-4 hexamethylene diacrylate

Oral LD50 > 5,000 mg/kg (rat)

Dermal LD50 > 3,000 mg/kg (rab)

Primary irritant effect:

on the skin: Caustic effect on skin and mucous membranes.

on the eye: Strong caustic effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Interactive effects No interactive effects between components are known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate: 2B

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Alternative sources for toxicological information

No non-standard sources for toxicological information were used.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

vPvB: Not applicable.

Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

*14 Transport information

UN-Number

DOT

not regulated

IMDG, IATA

UN3082

UN proper shipping name

DOT

not regulated

IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (2-phenoxyethyl acrylate, Neopentylglycol(PO)2 Diacrylate),
MARINE POLLUTANT

IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (2-phenoxyethyl acrylate, Neopentylglycol(PO)2 Diacrylate)

Transport hazard class(es)

DOT

Class

not regulated

IMDG, IATA



Class

9 Miscellaneous dangerous substances and articles

Label

9

Packing group

DOT

not regulated

IMDG, IATA

III

Environmental hazards:

Marine pollutant:

Symbol (fish and tree)

Special marking (IATA):

Symbol (fish and tree)

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

Transport/Additional information:

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Special precautions for user

Warning: Miscellaneous dangerous substances and articles

Hazard identification number (Kemler code): 90

EMS Number:

F-A,S-F

Stowage Category

A

UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-PHENOXYETHYL ACRYLATE, NEOPENTYLGlyCOL(PO)2 DIACRYLATE), 9, III

*15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

SARA

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

86273-46-3 2-Propenoic acid, 2-[2-(ethenoxy)ethoxy]ethyl ester: ACTIVE

48145-04-6 2-phenoxyethyl acrylate: ACTIVE

84170-74-1 Neopentylglycol(PO)2 Diacrylate: ACTIVE

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide: ACTIVE

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid: ACTIVE

13048-33-4 hexamethylene diacrylate: ACTIVE

Hazardous Air Pollutants

67-56-1 methanol

Proposition 65

Chemicals known to cause cancer:

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

67-56-1 methanol

Carcinogenic categories

EPA (Environmental Protection Agency)

110-82-7 cyclohexane: I

TLV (Threshold Limit Value)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS05 GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

2-Propenoic acid, 2-[2-(ethenyloxy)ethoxy]ethyl ester
Tetrahydrofurfuryl Acrylate
2-phenoxyethyl acrylate
diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
Neopentylglycol(PO)₂ Diacrylate
propylidynetrimethanol, propoxylated, esters with acrylic acid
hexamethylene diacrylate

Hazard statements

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May damage fertility or the unborn child.

Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
If swallowed: Call a poison center/doctor if you feel unwell.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H227 Combustible liquid.
H302 Harmful if swallowed.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 08/08/2025

Version: 2.0

Reviewed on 08/08/2025

Product name: ADapt G5/G6, UVInk, Varnish, L

H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H360 May damage fertility or the unborn child.
 H361 Suspected of damaging fertility or the unborn child.

Date of previous version 09/15/2022

Version number of previous version: 1.0

Date of preparation 08/08/2025

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flammable liquids 4: Flammable liquids – Category 4
 Acute toxicity - oral 4: Acute toxicity – Category 4
 Skin corrosion 1C: Skin corrosion/irritation – Category 1C
 Skin irritation 2: Skin corrosion/irritation – Category 2
 Eye damage 1: Serious eye damage/eye irritation – Category 1
 Eye irritation 2A: Serious eye damage/eye irritation – Category 2A
 Sensitization - skin 1: Skin sensitisation – Category 1
 Sensitization - skin 1A: Skin sensitisation – Category 1A
 Sensitization - skin 1B: Skin sensitisation – Category 1B
 Reproductive toxicity 1B: Reproductive toxicity – Category 1B
 Reproductive toxicity 2: Reproductive toxicity – Category 2

*** Data compared to the previous version altered.**